

EG800Q&EG91xQ Series

PSM&eDRX Application Note

LTE Standard Module Series

Version: 1.0

Date: 2024-08-20

Status: Released



At Quectel, our aim is to provide timely and comprehensive services to our customers. If you require any assistance, please contact our headquarters:

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

Tel: +86 21 5108 6236

Email: info@quectel.com

Or our local offices. For more information, please visit:

<http://www.quectel.com/support/sales.htm>.

For technical support, or to report documentation errors, please visit:

<http://www.quectel.com/support/technical.htm>.

Or email us at: support@quectel.com.

Legal Notices

We offer information as a service to you. The provided information is based on your requirements and we make every effort to ensure its quality. You agree that you are responsible for using independent analysis and evaluation in designing intended products, and we provide reference designs for illustrative purposes only. Before using any hardware, software or service guided by this document, please read this notice carefully. Even though we employ commercially reasonable efforts to provide the best possible experience, you hereby acknowledge and agree that this document and related services hereunder are provided to you on an “as available” basis. We may revise or restate this document from time to time at our sole discretion without any prior notice to you.

Use and Disclosure Restrictions

License Agreements

Documents and information provided by us shall be kept confidential, unless specific permission is granted. They shall not be accessed or used for any purpose except as expressly provided herein.

Copyright

Our and third-party products hereunder may contain copyrighted material. Such copyrighted material shall not be copied, reproduced, distributed, merged, published, translated, or modified without prior written consent. We and the third party have exclusive rights over copyrighted material. No license shall be granted or conveyed under any patents, copyrights, trademarks, or service mark rights. To avoid ambiguities, purchasing in any form cannot be deemed as granting a license other than the normal non-exclusive, royalty-free license to use the material. We reserve the right to take legal action for noncompliance with abovementioned requirements, unauthorized use, or other illegal or malicious use of the material.

Trademarks

Except as otherwise set forth herein, nothing in this document shall be construed as conferring any rights to use any trademark, trade name or name, abbreviation, or counterfeit product thereof owned by Quectel or any third party in advertising, publicity, or other aspects.

Third-Party Rights

This document may refer to hardware, software and/or documentation owned by one or more third parties ("third-party materials"). Use of such third-party materials shall be governed by all restrictions and obligations applicable thereto.

We make no warranty or representation, either express or implied, regarding the third-party materials, including but not limited to any implied or statutory, warranties of merchantability or fitness for a particular purpose, quiet enjoyment, system integration, information accuracy, and non-infringement of any third-party intellectual property rights with regard to the licensed technology or use thereof. Nothing herein constitutes a representation or warranty by us to either develop, enhance, modify, distribute, market, sell, offer for sale, or otherwise maintain production of any our products or any other hardware, software, device, tool, information, or product. We moreover disclaim any and all warranties arising from the course of dealing or usage of trade.

Privacy Policy

To implement module functionality, certain device data are uploaded to Quectel's or third-party's servers, including carriers, chipset suppliers or customer-designated servers. Quectel, strictly abiding by the relevant laws and regulations, shall retain, use, disclose or otherwise process relevant data for the purpose of performing the service only or as permitted by applicable laws. Before data interaction with third parties, please be informed of their privacy and data security policy.

Disclaimer

- a) We acknowledge no liability for any injury or damage arising from the reliance upon the information.
- b) We shall bear no liability resulting from any inaccuracies or omissions, or from the use of the information contained herein.
- c) While we have made every effort to ensure that the functions and features under development are free from errors, it is possible that they could contain errors, inaccuracies, and omissions. Unless otherwise provided by valid agreement, we make no warranties of any kind, either implied or express, and exclude all liability for any loss or damage suffered in connection with the use of features and functions under development, to the maximum extent permitted by law, regardless of whether such loss or damage may have been foreseeable.
- d) We are not responsible for the accessibility, safety, accuracy, availability, legality, or completeness of information, advertising, commercial offers, products, services, and materials on third-party websites and third-party resources.

Copyright © Quectel Wireless Solutions Co., Ltd. 2024. All rights reserved.

About the Document

Revision History

Version	Date	Author	Description
-	2023-11-03	Obuntu QIN	Creation of the document
1.0	2024-08-20	Obuntu QIN	First official release

Contents

About the Document.....	3
Contents	4
Table Index.....	5
1 Introduction	6
2 Overview of PSM and eDRX.....	7
2.1. PSM Introduction.....	7
2.2. eDRX Introduction.....	7
3 Description of AT Commands	9
3.1. AT Command Introduction	9
3.1.1. Definitions.....	9
3.1.2. AT Command Syntax	9
3.2. Declaration of AT Command Examples	10
3.3. Description of PSM AT Commands	10
3.3.1. AT+CPSMS Set Power Saving Mode	10
3.3.2. AT+QPSMS Set Power Saving Mode (Extended)	12
3.3.3. AT+QCFG="psm/urc" Enable/Disable PSM Entering Indication	14
3.4. Description of eDRX AT Commands	15
3.4.1. AT+CEDRXS Set eDRX Parameters	15
3.4.2. AT+QPTWEDRXS Set Paging Time Window and eDRX Cycle Values.....	18
3.4.3. AT+CEDRXRDP Read eDRX Dynamic Parameters	21
4 Summary of Error Codes	24
5 Appendix References	26

Table Index

Table 1: Types of AT Commands	9
Table 2: Different Coding Schemes of +CME ERROR: <err>	24
Table 3: Related Document	26
Table 4: Terms and Abbreviations	26

1 Introduction

This document outlines PSM and eDRX features and describes how to use the PSM and eDRX features of Quectel EG800Q series and EG91xQ family (EG915Q series and EG916Q-GL) modules through related AT commands.

2 Overview of PSM and eDRX

2.1. PSM Introduction

The PSM, as defined by 3GPP Release 12, operates similarly to a power-off state, yet it allows the UE, such as the EG800Q series and EG91xQ family modules, to maintain network registration without the necessity for re-attaching or re-establishing PDN connections. Despite this, the UE in PSM is not immediately accessible for mobile terminating services. When the UE is in PSM, it becomes available for mobile terminating services during its connected mode, as well as for a certain duration of the Active Time that follows the connected mode. The transition to connected mode can be triggered by mobile originated events, such as data transmission or signaling, for instance, after a periodic TAU process.

Consequently, PSM is ideal for UEs that anticipate infrequent mobile originating and terminating services and can tolerate a degree of latency in the mobile terminating communication.

NOTE

For more details regarding PSM mode defined by 3GPP Release 12, see *3GPP TS 23.682 clause 4.5.4 UE Power Saving Mode*.

2.2. eDRX Introduction

eDRX is introduced in *3GPP Release 13* as an extension of the DRX feature used by IoT devices for reducing power consumption.

- DRX is a mechanism that puts a device to sleep and subsequently wakes it up after a fixed interval to receive downlink data.
- The basic principle of eDRX is to extend idle mode DRX cycles to allow the device to remain in a power-saving state for an extended period.

Applications that use extended idle mode DRX must carefully handle mobile-terminating services or data transfers, and in particular they need to consider the delay tolerance of mobile terminated data. A network side application may send mobile terminated data, an SMS, or a device trigger, and needs to be aware that extended idle mode DRX may be in place. A UE should request extended idle mode DRX only when all expected mobile terminating communication is tolerant to delay.¹⁾

The eDRX parameters include paging time window (PTW) and eDRX cycle. UE should include the expected eDRX parameter IE in an **Attach Request** or **Tracking Area Update Request** message to indicate that the UE supports the idle eDRX feature. If the network supports the eDRX feature, it will include the corresponding eDRX parameter values in the **Attach Accept** or **Tracking Area Update Accept** message sent to the UE. Regarding E-UTRAN network, it should include "eDRX-Allowed-r13 <true>" IE in system information. If this IE is not present, it should be assumed that the network does not support the eDRX feature.




Figure 1: eDRX Feature Overview

NOTE

1. ¹⁾ Quoted from 3GPP TS 23.682 technical specification. For more information on eDRX mode, see 3GPP TS 23.682, clause 4.5.13 Extended idle mode DRX.
2. The Paging Time Window (PTW) is not started by receiving an RRC release and starts from the next Paging Occasion (PO). The calculation of PO is primarily determined by the UE_ID (IMSI). For more details, see 3GPP TS36.304, clause 7 Paging.

3 Description of AT Commands

3.1. AT Command Introduction

3.1.1. Definitions

- **<CR>** Carriage return character.
- **<LF>** Line feed character.
- **<...>** Parameter name. Angle brackets do not appear on the command line.
- **[...]** Optional parameter of a command or an optional part of TA information response. Square brackets do not appear on the command line. When an optional parameter is not given in a command, the new value equals its previous value or the default settings, unless otherwise specified.
- **Underline** Default setting of a parameter.

3.1.2. AT Command Syntax

All command lines must start with **AT** or **at** and end with **<CR>**. Information responses and result codes always start and end with a carriage return character and a line feed character: **<CR><LF><response><CR><LF>**. In tables presenting commands and responses throughout this document, only the commands and responses are presented, and **<CR>** and **<LF>** are deliberately omitted.

Table 1: Types of AT Commands

Command Type	Syntax	Description
Test Command	AT+<cmd>=?	Test the existence of corresponding command and return information about the type, value, or range of its parameter.
Read Command	AT+<cmd>?	Check the current parameter value of a corresponding command.
Write Command	AT+<cmd>=<p1>[,<p2>[,<p3>[...]]]	Set user-definable parameter value.
Execution Command	AT+<cmd>	Return a specific information parameter or perform a specific action.

3.2. Declaration of AT Command Examples

The AT command examples in this document are provided to help you learn about the use of the AT commands introduced herein. The examples, however, should not be taken as Quectel's recommendations or suggestions about how to design a program flow or what status to set the module into. Sometimes multiple examples may be provided for one AT command. However, this does not mean that there is a correlation among these examples, or that they should be executed in a given sequence.

3.3. Description of PSM AT Commands

3.3.1. AT+CPSMS Set Power Saving Mode

The Write Command configures PSM parameters of the module. It controls whether the module wants to apply PSM or not, as well as configures the requested extended periodic TAU value and Active Time value in E-UTRAN.

AT+CPSMS Set Power Saving Mode	
Test Command AT+CPSMS=?	Response +CPSMS: (range of supported <mode>s),,(list of supported <Requested_Periodic-TAU>s),(list of supported <Requested_Active-Time>s) OK
Read Command AT+CPSMS?	Response +CPSMS: <mode> ,,[[<Requested_Periodic-TAU>], [<Requested_Active-Time>] OK
Write Command AT+CPSMS=[<mode>],[<Requested_Periodic-TAU>],[<Requested_Active-Time>]]	Response OK If there is any error: ERROR
Maximum Response Time	300 ms
Characteristics	The command takes effect immediately. The configurations are saved automatically.
Reference 3GPP TS 27.007	/

Parameter

<mode>	<p>Integer type. Disable or enable the use of PSM in the UE.</p> <p>0 Disable the use of PSM</p> <p>1 Enable the use of PSM</p> <p>2 Disable the use of PSM and discard all parameters for PSM configuration</p>
<Requested_Periodic-TAU>	<p>String type. One byte in an 8-bit format. Requested extended periodic TAU value (T3412) to be allocated to the UE in E-UTRAN (e.g. "00001010" equals 100 minutes.). In the Write Command, when <mode> is 1 and <Requested_Periodic-TAU> is omitted, the last configured value is used.</p> <p>Bits 5 to 1 represent the binary coded timer value.</p> <p>Bits 6 to 8 define the timer value unit as follows:</p> <p>Bits 8 7 6</p> <p>0 0 0 value is incremented in multiples of 10 minutes</p> <p>0 0 1 value is incremented in multiples of 1 hour</p> <p>0 1 0 value is incremented in multiples of 10 hours</p> <p>0 1 1 value is incremented in multiples of 2 seconds</p> <p>1 0 0 value is incremented in multiples of 30 seconds</p> <p>1 0 1 value is incremented in multiples of 1 minute</p> <p>1 1 0 value is incremented in multiples of 320 hours</p> <p>1 1 1 value indicates that the timer is deactivated</p>
<Requested_Active-Time>	<p>String type. One byte in an 8-bit format. Requested Active Time value (T3324) to be allocated to the UE. (e.g. "00011110" equals 1 minute.).</p> <p>Bits 5 to 1 represent the binary coded timer value.</p> <p>Bits 6 to 8 define the timer value unit as follows:</p> <p>Bits 8 7 6</p> <p>0 0 0 value is incremented in multiples of 2 seconds</p> <p>0 0 1 value is incremented in multiples of 1 minute</p> <p>0 1 0 value is incremented in multiples of decihours</p> <p>1 1 1 value indicates that the timer is deactivated</p>

Example

```
AT+CPSMS=1,,,"00000100","00001111" //Set the requested T3412 value to 40 minutes, and set the
OK requested T3324 value to 30 seconds.
```

3.3.2. AT+QPSMS Set Power Saving Mode (Extended)

This is an extended AT command for setting PSM parameters, which was developed by Quectel. A special form of the command can be run as **AT+QPSMS=** (with all parameters omitted). In this form, the use of PSM is disabled (**<mode>=0**) and data for all parameters in the command are removed. It is similar to **AT+CPSMS**.

AT+QPSMS Set Power Saving Mode (Extended)	
Test Command AT+QPSMS=?	Response +QPSMS: (list of supported <mode>s),,(list of supported <Requested_Periodic-TAU>s),(list of supported <Requested_Active-Time>s) OK
Read Command AT+QPSMS?	Response +QPSMS: <mode> ,,,[<Network_Periodic-TAU>],[<Network_Active-Time>] OK
Write Command AT+QPSMS=[<mode>],[<Requested_Periodic-TAU>],[<Requested_Active-Time>]]	Response OK If there is any error: ERROR
Maximum Response Time	300 ms
Characteristics	The command takes effect immediately. The configurations are saved automatically.
Reference 3GPP TS 27.007	/

Parameter

<mode>	Integer type. Disable or enable the use of PSM in the UE. 0 Disable the use of PSM 1 Enable the use of PSM
<Requested_Periodic-TAU>	String type. One byte in an 8-bit format. Requested extended periodic TAU value (T3412) to be allocated to the UE in E-UTRAN (e.g. "00001010" equals 100 minutes.). Bits 5 to 1 represent the binary coded timer value. Bits 6 to 8 define the timer value unit as follows: Bits 8 7 6 0 0 0 value is incremented in multiples of 10 minutes 0 0 1 value is incremented in multiples of 1 hour

	0 1 0	value is incremented in multiples of 10 hours
	0 1 1	value is incremented in multiples of 2 seconds
	1 0 0	value is incremented in multiples of 30 seconds
	1 0 1	value is incremented in multiples of 1 minute
	1 1 0	value is incremented in multiples of 320 hours
	1 1 1	value indicates that the timer is deactivated
<Requested_Active-Time>	String type. One byte in an 8-bit format. Requested Active Time value (T3324) to be allocated to the UE. (e.g. "00011110" equals to 1 minute.). Bits 5 to 1 represent the binary coded timer value. Bits 6 to 8 define the timer value unit as follows: Bits 8 7 6 0 0 0 value is incremented in multiples of 2 seconds 0 0 1 value is incremented in multiples of 1 minute 0 1 0 value is incremented in multiples of decihours 1 1 1 value indicates that the timer is deactivated	
<Network_Periodic-TAU>	Integer type. Extended periodic TAU value (T3412) to be allocated to the UE in E-UTRAN, and the value is specified by network. Unit: second.	
<Network_Active-Time>	Integer type. Active timer value (T3324) to be allocated to the UE in E-UTRAN, and the value is specified by network. Unit: second.	

NOTE

If the network has already set **<Network_Periodic-TAU>** and **<Network_Active-Time>**, you can use **AT+QPSMS?** to query the current values of these timers. If the network has not yet allocated these two parameters, executing this command will return **+QPSMS: 1,,,**.

Example

```

AT+QPSMS=1,,"00000100","00001111" //Set the requested T3412 value to 40 minutes, and set the
                                     requested T3324 value to 30 seconds.
OK
AT+QPSMS?                             //Query the PSM mode and the periodic-TAU and active
                                     time specified by the network.
+QPSMS: 1,,86400,2
OK

```

3.3.3. AT+QCFG="psm/urc" Enable/Disable PSM Entering Indication

The command enables/disables the output of URC **+QPSMTIMER: <TAU_timer>,<T3324_timer>**, which indicates the interval for periodic TAU and active time duration before the module enters PSM.

When PSM function is enabled and RRC connection release is received, the active timer (T3324) is started, and the indication URC is reported.

AT+QCFG="psm/urc" Enable/Disable PSM Entering Indication	
Write Command AT+QCFG="psm/urc"[,<enable>]	<p>Response</p> <p>If the optional parameter is omitted, query the current setting: +QCFG: "psm/urc",<enable></p> <p>OK</p> <p>If the optional parameter is specified, set whether to enable PSM entering indication. OK</p> <p>If there is an error related to ME functionality: +CME ERROR: <err></p> <p>If there is any other error: ERROR</p>
Maximum Response Time	300 ms
Characteristics	<p>The command takes effect immediately.</p> <p>The configuration is saved automatically.</p>

Parameter

<enable>	Integer type. Enable/disable the output of URC +QPSMTIMER: <TAU_timer>,<T3324_timer> . If enabled, the URC is reported when RRC connection release is received. 0 Disable 1 Enable
<TAU_timer>	Integer type. Interval for periodic tracking area updating. Unit: second.
<T3324_timer>	Integer type. Active time duration before the module enters PSM. Unit: second.
<err>	Error code. See Chapter 4 for details.

Example

```
AT+QCFG="psm/urc"
+QCFG: "psm/urc",0

OK
AT+QCFG="psm/urc",1
OK

+QPSMTIMER: 86400,2 //Interval for periodic TAU and active time duration.
```

3.4. Description of eDRX AT Commands

3.4.1. AT+CEDRXS Set eDRX Parameters

This command sets the UE's eDRX parameters. It allows the UE to specify whether to apply eDRX or not, as well as the requested eDRX cycle value for each specified access technology.

It also controls the presentation of the URC **+CEDRXP:** **<AcT>[,<Requested_eDRX_value>[,<NW-provided_eDRX_value>[,<Paging_time_window>]]]** when **<mode>=2** and there is a change in the eDRX parameters provided by the network.

A special form of the command can be given as **AT+CEDRXS=3**. In this form, eDRX is disabled and all parameters configured by **AT+CEDRXS** are deleted.

AT+CEDRXS Set eDRX Parameters	
Test Command AT+CEDRXS=?	Response +CEDRXS: (range of supported <mode>s),(list of supported <AcT>s),(list of supported <Requested_eDRX_value>s) OK
Read Command AT+CEDRXS?	Response +CEDRXS: <AcT>[,<Requested_eDRX_value>] OK
Write Command AT+CEDRXS=<mode>[,<AcT>[,<Requested_eDRX_value>]]	Response OK If there is any error: ERROR
Maximum Response Time	300 ms
Characteristics	This command takes effect immediately.

	The configurations are saved automatically.
Reference 3GPP TS 27.007	/

Parameter

<mode>	Integer type. Disable or enable the use of eDRX in the UE.				
0	Disable the use of eDRX				
1	Enable the use of eDRX				
2	Enable the use of eDRX and enable the URC				
	+CEDRXP: <AcT>[,<Requested_eDRX_value>[,<NW-provided_eDRX_value>[,<Paging_time_window>]]]				
3	Disable eDRX and discard all parameters for eDRX configuration				
<AcT>	Integer type. Type of access technology.				
0	Access technology is not using eDRX. This parameter value is only used in the URC.				
4	E-UTRAN (WB-S1 mode)				
<Requested_eDRX_value>	String type. Half a byte in a 4-bit format. eDRX cycle requested by UE.				
	Bit				Description
	4	3	2	1	E-UTRAN eDRX cycle
	0	0	0	0	5.12 seconds
	0	0	0	1	10.24 seconds
	0	0	1	0	20.48 seconds
	0	0	1	1	40.96 seconds
	0	1	0	0	61.44 seconds
	0	1	0	1	81.92 seconds
	0	1	1	0	102.4 seconds
	0	1	1	1	122.88 seconds
	1	0	0	0	143.36 seconds
	1	0	0	1	163.84 seconds
	1	0	1	0	327.68 seconds
	1	0	1	1	655.36 seconds
	1	1	0	0	1310.72 seconds
	1	1	0	1	2621.44 seconds
	1	1	1	0	5242.88 seconds
	1	1	1	1	10485.76 seconds
<NW-provided_eDRX_value>	String type. Half a byte in a 4-bit format. eDRX cycle issued by the network.				
	Bit				Description
	4	3	2	1	E-UTRAN eDRX cycle
	0	0	0	0	5.12 seconds
	0	0	0	1	10.24 seconds
	0	0	1	0	20.48 seconds

0	0	1	1	40.96 seconds
0	1	0	0	61.44 seconds
0	1	0	1	81.92 seconds
0	1	1	0	102.4 seconds
0	1	1	1	122.88 seconds
1	0	0	0	143.36 seconds
1	0	0	1	163.84 seconds
1	0	1	0	327.68 seconds
1	0	1	1	655.36 seconds
1	1	0	0	1310.72 seconds
1	1	0	1	2621.44 seconds
1	1	1	0	5242.88 seconds
1	1	1	1	10485.76 seconds

<Paging_time_window>

String type. Half a byte in a 4-bit format. Paging time window issued by the network.

Bit				Description
4	3	2	1	PTW length
0	0	0	0	1.28 seconds
0	0	0	1	2.56 seconds
0	0	1	0	3.84 seconds
0	0	1	1	5.12 seconds
0	1	0	0	6.4 seconds
0	1	0	1	7.68 seconds
0	1	1	0	8.96 seconds
0	1	1	1	10.24 seconds
1	0	0	0	11.52 seconds
1	0	0	1	12.8 seconds
1	0	1	0	14.08 seconds
1	0	1	1	15.36 seconds
1	1	0	0	16.64 seconds
1	1	0	1	17.92 seconds
1	1	1	0	19.20 seconds
1	1	1	1	20.48 seconds

Example

```

AT+CEDRXS=1,4,"0000" //Set the requested eDRX cycle to 5.12 seconds.
OK
AT+CEDRXS=0,4 //Disable eDRX function.
OK
AT+CEDRXS=2,4,"0000" //Set the requested eDRX cycle to 5.12 seconds and enable
the URC.
OK
+CEDRXP: 4,"0000","0000","0000" //Network accepted the eDRX parameters.

```

3.4.2. AT+QPTWEDRXS Set Paging Time Window and eDRX Cycle Values

This command controls the setting of the UE's PTW value and eDRX parameters. It allows the UE to specify whether to apply PTW and eDRX, and also provides the requested PTW and eDRX cycle parameter values for each specified access technology.

Additionally, the command controls the presentation of the URC **+QPTWEDRXP:** **<AcT>[,<Requested_paging_time_window>[,<Requested_eDRX_value>[,<NW-provided_eDRX_value>[,<Paging_time_window>]]]]**, which is triggered when **<mode>=2** and there is a change in the paging time window and eDRX parameters provided by the network.

A special form of the command can be given as **AT+QPTWEDRXS=3**. In this form, PTW and eDRX are disabled and all parameters configured by **AT+QPTWEDRXS** are deleted.

AT+QPTWEDRXS Set Paging Time Window and eDRX Cycle Values	
Test Command AT+QPTWEDRXS=?	Response +QPTWEDRXS: (range of supported <mode>s),(list of supported <AcT>s),(range of supported <Requested_paging_time_window>s),(range of supported <Requested_eDRX_value>s) OK
Read Command AT+QPTWEDRXS?	Response +QPTWEDRXS: <AcT>[,<Requested_paging_time_window>,<Requested_eDRX_value>[,<NW-provided_eDRX_value>[,<Paging_time_window>]]] [...] OK Or ERROR

	0	1	1	1	10.24 seconds
	1	0	0	0	11.52 seconds
	1	0	0	1	12.8 seconds
	1	0	1	0	14.08 seconds
	1	0	1	1	15.36 seconds
	1	1	0	0	16.64 seconds
	1	1	0	1	17.92 seconds
	1	1	1	0	19.20 seconds
	1	1	1	1	20.48 seconds
<Requested_eDRX_value>	String type. Half a byte in a 4-bit format. eDRX cycle requested by UE.				
	Bit				Description
	4	3	2	1	E-UTRAN eDRX cycle
	0	0	0	0	5.12 seconds
	0	0	0	1	10.24 seconds
	0	0	1	0	20.48 seconds
	0	0	1	1	40.96 seconds
	0	1	0	0	61.44 seconds
	0	1	0	1	81.92 seconds
	0	1	1	0	102.4 seconds
	0	1	1	1	122.88 seconds
	1	0	0	0	143.36 seconds
	1	0	0	1	163.84 seconds
	1	0	1	0	327.68 seconds
	1	0	1	1	655.36 seconds
	1	1	0	0	1310.72 seconds
	1	1	0	1	2621.44 seconds
	1	1	1	0	5242.88 seconds
	1	1	1	1	10485.76 seconds
<NW-provided_eDRX_value>	String type. Half a byte in a 4-bit format. eDRX cycle issued by the network.				
	Bit				Description
	4	3	2	1	E-UTRAN eDRX cycle
	0	0	0	0	5.12 seconds
	0	0	0	1	10.24 seconds
	0	0	1	0	20.48 seconds
	0	0	1	1	40.96 seconds
	0	1	0	0	61.44 seconds
	0	1	0	1	81.92 seconds
	0	1	1	0	102.4 seconds
	0	1	1	1	122.88 seconds
	1	0	0	0	143.36 seconds
	1	0	0	1	163.84 seconds
	1	0	1	0	327.68 seconds

	1	0	1	1	655.36 seconds
	1	1	0	0	1310.72 seconds
	1	1	0	1	2621.44 seconds
	1	1	1	0	5242.88 seconds
	1	1	1	1	10485.76 seconds
<Paging_time_window>	String type. Half a byte in a 4-bit format. Paging time window issued by the network.				
	Bit				Description
	4	3	2	1	PTW length
	0	0	0	0	1.28 seconds
	0	0	0	1	2.56 seconds
	0	0	1	0	3.84 seconds
	0	0	1	1	5.12 seconds
	0	1	0	0	6.4 seconds
	0	1	0	1	7.68 seconds
	0	1	1	0	8.96 seconds
	0	1	1	1	10.24 seconds
	1	0	0	0	11.52 seconds
	1	0	0	1	12.8 seconds
	1	0	1	0	14.08 seconds
	1	0	1	1	15.36 seconds
	1	1	0	0	16.64 seconds
	1	1	0	1	17.92 seconds
	1	1	1	0	19.20 seconds
	1	1	1	1	20.48 seconds
<err>	Error code. See Chapter 4 for details.				

3.4.3. AT+CEDRXRDP Read eDRX Dynamic Parameters

The Execution Command returns **+CEDRXRDP:** <AcT>[,<Requested_eDRX_value>[,<NW-provided_eDRX_value>[,<Paging_time_window>]]] if the cell in which the UE is registered has enabled eDRX. The Execution Command only responds with **+CEDRXRDP: 0** if the cell in which the UE is registered does not support eDRX.

AT+CEDRXRDP Read eDRX Dynamic Parameters	
Test Command AT+CEDRXRDP=?	Response OK
Execution Command AT+CEDRXRDP	Response +CEDRXRDP: <AcT>[,<Requested_eDRX_value>[,<NW-provided_eDRX_value>[,<Paging_time_window>]]] OK
Maximum Response Time	300 ms

Characteristics	/
Reference 3GPP TS 27.007	/

Parameter

<AcT>	Integer type. Type of access technology.																																																																																													
	0 Access technology is not using eDRX																																																																																													
	4 E-UTRAN (WB-S1 mode)																																																																																													
<Requested_eDRX_value>	String type. Half a byte in a 4-bit format. eDRX cycle requested by UE.																																																																																													
	<table> <tr> <th colspan="4">Bit</th><th>Description</th></tr> <tr> <th>4</th><th>3</th><th>2</th><th>1</th><th>E-UTRAN eDRX cycle</th></tr> <tr><td>0</td><td>0</td><td>0</td><td>0</td><td>5.12 seconds</td></tr> <tr><td>0</td><td>0</td><td>0</td><td>1</td><td>10.24 seconds</td></tr> <tr><td>0</td><td>0</td><td>1</td><td>0</td><td>20.48 seconds</td></tr> <tr><td>0</td><td>0</td><td>1</td><td>1</td><td>40.96 seconds</td></tr> <tr><td>0</td><td>1</td><td>0</td><td>0</td><td>61.44 seconds</td></tr> <tr><td>0</td><td>1</td><td>0</td><td>1</td><td>81.92 seconds</td></tr> <tr><td>0</td><td>1</td><td>1</td><td>0</td><td>102.4 seconds</td></tr> <tr><td>0</td><td>1</td><td>1</td><td>1</td><td>122.88 seconds</td></tr> <tr><td>1</td><td>0</td><td>0</td><td>0</td><td>143.36 seconds</td></tr> <tr><td>1</td><td>0</td><td>0</td><td>1</td><td>163.84 seconds</td></tr> <tr><td>1</td><td>0</td><td>1</td><td>0</td><td>327.68 seconds</td></tr> <tr><td>1</td><td>0</td><td>1</td><td>1</td><td>655.36 seconds</td></tr> <tr><td>1</td><td>1</td><td>0</td><td>0</td><td>1310.72 seconds</td></tr> <tr><td>1</td><td>1</td><td>0</td><td>1</td><td>2621.44 seconds</td></tr> <tr><td>1</td><td>1</td><td>1</td><td>0</td><td>5242.88 seconds</td></tr> <tr><td>1</td><td>1</td><td>1</td><td>1</td><td>10485.76 seconds</td></tr> </table>				Bit				Description	4	3	2	1	E-UTRAN eDRX cycle	0	0	0	0	5.12 seconds	0	0	0	1	10.24 seconds	0	0	1	0	20.48 seconds	0	0	1	1	40.96 seconds	0	1	0	0	61.44 seconds	0	1	0	1	81.92 seconds	0	1	1	0	102.4 seconds	0	1	1	1	122.88 seconds	1	0	0	0	143.36 seconds	1	0	0	1	163.84 seconds	1	0	1	0	327.68 seconds	1	0	1	1	655.36 seconds	1	1	0	0	1310.72 seconds	1	1	0	1	2621.44 seconds	1	1	1	0	5242.88 seconds	1	1	1	1	10485.76 seconds
Bit				Description																																																																																										
4	3	2	1	E-UTRAN eDRX cycle																																																																																										
0	0	0	0	5.12 seconds																																																																																										
0	0	0	1	10.24 seconds																																																																																										
0	0	1	0	20.48 seconds																																																																																										
0	0	1	1	40.96 seconds																																																																																										
0	1	0	0	61.44 seconds																																																																																										
0	1	0	1	81.92 seconds																																																																																										
0	1	1	0	102.4 seconds																																																																																										
0	1	1	1	122.88 seconds																																																																																										
1	0	0	0	143.36 seconds																																																																																										
1	0	0	1	163.84 seconds																																																																																										
1	0	1	0	327.68 seconds																																																																																										
1	0	1	1	655.36 seconds																																																																																										
1	1	0	0	1310.72 seconds																																																																																										
1	1	0	1	2621.44 seconds																																																																																										
1	1	1	0	5242.88 seconds																																																																																										
1	1	1	1	10485.76 seconds																																																																																										
<NW_provided_eDRX_value>	String type. Half a byte in a 4-bit format. eDRX cycle issued by the network.																																																																																													
	<table> <tr> <th colspan="4">Bit</th><th>Description</th></tr> <tr> <th>4</th><th>3</th><th>2</th><th>1</th><th>E-UTRAN eDRX cycle</th></tr> <tr><td>0</td><td>0</td><td>0</td><td>0</td><td>5.12 seconds</td></tr> <tr><td>0</td><td>0</td><td>0</td><td>1</td><td>10.24 seconds</td></tr> <tr><td>0</td><td>0</td><td>1</td><td>0</td><td>20.48 seconds</td></tr> <tr><td>0</td><td>0</td><td>1</td><td>1</td><td>40.96 seconds</td></tr> <tr><td>0</td><td>1</td><td>0</td><td>0</td><td>61.44 seconds</td></tr> <tr><td>0</td><td>1</td><td>0</td><td>1</td><td>81.92 seconds</td></tr> <tr><td>0</td><td>1</td><td>1</td><td>0</td><td>102.4 seconds</td></tr> <tr><td>0</td><td>1</td><td>1</td><td>1</td><td>122.88 seconds</td></tr> <tr><td>1</td><td>0</td><td>0</td><td>0</td><td>143.36 seconds</td></tr> <tr><td>1</td><td>0</td><td>0</td><td>1</td><td>163.84 seconds</td></tr> <tr><td>1</td><td>0</td><td>1</td><td>0</td><td>327.68 seconds</td></tr> </table>				Bit				Description	4	3	2	1	E-UTRAN eDRX cycle	0	0	0	0	5.12 seconds	0	0	0	1	10.24 seconds	0	0	1	0	20.48 seconds	0	0	1	1	40.96 seconds	0	1	0	0	61.44 seconds	0	1	0	1	81.92 seconds	0	1	1	0	102.4 seconds	0	1	1	1	122.88 seconds	1	0	0	0	143.36 seconds	1	0	0	1	163.84 seconds	1	0	1	0	327.68 seconds																									
Bit				Description																																																																																										
4	3	2	1	E-UTRAN eDRX cycle																																																																																										
0	0	0	0	5.12 seconds																																																																																										
0	0	0	1	10.24 seconds																																																																																										
0	0	1	0	20.48 seconds																																																																																										
0	0	1	1	40.96 seconds																																																																																										
0	1	0	0	61.44 seconds																																																																																										
0	1	0	1	81.92 seconds																																																																																										
0	1	1	0	102.4 seconds																																																																																										
0	1	1	1	122.88 seconds																																																																																										
1	0	0	0	143.36 seconds																																																																																										
1	0	0	1	163.84 seconds																																																																																										
1	0	1	0	327.68 seconds																																																																																										

	1	0	1	1	655.36 seconds
	1	1	0	0	1310.72 seconds
	1	1	0	1	2621.44 seconds
	1	1	1	0	5242.88 seconds
	1	1	1	1	10485.76 seconds
<Paging_time_window>	String type. Half a byte in a 4-bit format. Paging time window issued by the network.				
	Bit				Description
	4	3	2	1	PTW length
	0	0	0	0	1.28 seconds
	0	0	0	1	2.56 seconds
	0	0	1	0	3.84 seconds
	0	0	1	1	5.12 seconds
	0	1	0	0	6.4 seconds
	0	1	0	1	7.68 seconds
	0	1	1	0	8.96 seconds
	0	1	1	1	10.24 seconds
	1	0	0	0	11.52 seconds
	1	0	0	1	12.8 seconds
	1	0	1	0	14.08 seconds
	1	0	1	1	15.36 seconds
	1	1	0	0	16.64 seconds
	1	1	0	1	17.92 seconds
	1	1	1	0	19.20 seconds
	1	1	1	1	20.48 seconds

Example

```

AT+CEDRXS=1,4,"0000" //Set the requested eDRX cycle to 5.12 seconds.
OK
AT+CEDRXRDP
+CEDRXRDP: 4,"0000","0000","0000" //Network accepted the eDRX parameters.

OK
AT+CEDRXS=0,4 //Disable eDRX feature.
OK
AT+CEDRXRDP
+CEDRXRDP: 0 //Access technology is not using eDRX.

OK

```


4 Summary of Error Codes

Final result code **+CME ERROR: <err>** indicates an error related to mobile equipment or network. It functions similarly to **ERROR** result code. If a command line receives this code, no further command in that line will be executed and no **ERROR** or **OK** result code will be returned.

<err> values are mostly used by common message commands. The following table lists related **ERROR** codes. However, **ERROR** codes of some GSM protocol failure causes described in GSM specifications are not provided in the table.

Table 2: Different Coding Schemes of +CME ERROR: <err>

Numeric <err> Value	Verbose <err> Value
3	operation not allowed
4	operation not supported
10	SIM not inserted
11	SIM PIN required
12	SIM PUK required
13	SIM failure
14	SIM busy
15	SIM wrong
16	incorrect password
17	SIM PIN2 required
18	SIM PUK2 required
20	memory full
21	invalid index
22	not found

23	memory failure
24	text string too long
30	no network service
31	network timeout

5 Appendix References

Table 3: Related Document

Document Name
[1] Quectel_EG800Q&EG91xQ_Series_AT_Commands_Manual

Table 4: Terms and Abbreviations

Abbreviation	Description
3GPP	3rd Generation Partnership Project
DRX	Discontinuous Reception
eDRX	Extended Discontinuous Reception
E-UTRAN	Evolved Universal Terrestrial Radio Access Network
IE	Information Element
IMSI	International Mobile Subscriber Identity
IoT	Internet of Things
PDN	Packet Data Network
PIN	Personal Identification Number
PO	Paging Occasion
PSM	Power Saving Mode
PTW	Paging Time Window
PUK	PIN Unlock Key
RRC	Radio Resource Control
SIM	Subscriber Identity Module
SMS	Short Message Service

TAU	Tracking Area Update
UE	User Equipment
URC	Unsolicited Result Code